

In the Claims:

1. (Currently amended) A method of performing an initial copy procedure in a remote copy system, the method comprising:
 - configuring a network path between a first disk subsystem and a second disk subsystem to increase the speed of data transmission across the network path;
 - configuring the remote copy system for a remote copy operation;
 - performing an initial remote copy operation to copy data across the network path from the first disk subsystem to the second disk subsystem; and
 - adjusting the network path to reduce the speed of data transmission across the network path, thereby reducing the speed of at least one subsequent remote copy operation between the first disk system and the second disk system.
2. (Original) The method of claim 1 wherein the first disk subsystem is located in a master site.
3. (Original) The method of claim 1 wherein the first disk subsystem is located in a manufacturer site.
4. (Original) The method of claim 1, further comprising:
 - deploying the second disk subsystem to a remote site.
5. (Original) The method of claim 1 wherein the configuring the remote copy system comprises:
 - selecting multiple physical paths in the network path to transmit data across the path.
6. (Original) The method of claim 1 wherein the configuring the remote copy system comprises:
 - increasing a data transfer rate characteristic of the network path.

7. (Original) The method of claim 1 wherein adjusting the network path comprises:
reducing the number of physical paths in the network path for transmitting data.
8. (Original) The method of claim 1 wherein adjusting the network path comprises:
decreasing the data transfer rate characteristic of the network path.
9. (Currently amended) An article of manufacture, comprising:
a machine-readable medium having stored thereon instructions to:
 configure a network path between a first disk subsystem and a second disk
subsystem to increase the speed of data transmission across the network path;
 configure the remote copy system for a remote copy operation;
 perform an initial remote copy operation to copy data across the network path
from the first disk subsystem to the second disk subsystem; and
 adjust the network path to reduce the speed of data transmission across the
network path and thereby reduce the speed of at least one subsequent remote copy operation
between the first disk system and the second disk system.
- 10-19. (Canceled)
20. (Currently amended) A remote copy system, comprising:
a first disk subsystem located at a first site;
a second disk subsystem capable to be coupled to the first disk subsystem via a network
path, with the network path capable to be configured to increase or decrease the speed of data
transmission from the first disk subsystem to the second disk subsystem; and
means for configuring the network path to cause an initial remote copy operation between
the first disk subsystem and the second disk subsystem to occur at an initial data transmission
speed that is faster than a subsequent data transmission speed of at least one subsequent remote
copy operation.
- 21-23. (Canceled)